



Practitioner's Docket No.: 327\_084

Pre.  
11/C  
T. Steptoe  
PATENT 5-24-03

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the application of:

Rudolf Flosbach

May 20, 2003

Ser. No.: 09/807,154

Art Unit: 2856

Filed: April 9, 2001

Examiner: Andre' K. Jackson

For: FILM LEAK DETECTOR

Mail Stop RCE  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

"EXPRESS MAIL" mailing label number EL 796815454 US.

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 addressed to the Mail Stop RCE, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on May 20, 2003.

*Susanne C. Aregano*  
Susanne C. Aregano

RCE PRELIMINARY AMENDMENT RESPONSE TO FINAL ACTION  
PURSUANT TO 37 CFR § 1.116

Sir:

In response to the final Office Action, Paper No. 9, dated February 20, 2003, please amend the above-captioned patent application, without prejudice, as follows:

**In the Claims:**

Please amend Claims 21-26 as follows:

21. (Amended) A frame structure for a leak detector, said frame structure comprising:

an upper frame and a lower frame onto each of which a film is stretched thereupon, each of the upper frame and the lower frame further comprising an outer subframe and an inner subframe each made from a synthetic material between which said films are fastened wherein each outer subframe of said upper and lower frames, respectively, includes a recess having disposed therein a corresponding inner subframe thereby defining a test chamber between said upper and lower frames for an incoming test gas sample entering said defined test chamber and in which said films are at least one of adhered and screw-fastened with the frame portions onto which they are respectively stretched and in which each recess is disposed in a region of a corresponding outer subframe facing away from the test chamber and wherein one of said inner subframes is equipped with a lip seal, said lower frame being positioned onto a margin of a plate-form bottom, said upper frame including a support provided with a steel profile, said steel profile

RECEIVED  
MAY 22 2003  
TECHNOLOGY CENTER 2800

C1  
cont